## CLAIM AMENDMENTS

## IN THE CLAIMS

This listing of the claims will replace all prior versions, and listing, of claims in the application or previous response to office action:

- 1. (Currently Amended) A battery-powered system for acquiring and transmitting data between two or more plant locations relative to [[a]] detected conditions and/or events in a plant, said system comprising:
- at least <u>first and second</u> [[one]] detectors in said plant to detect [[a]] conditions or events, <u>the detectors</u> mounted at [[a]] first <u>and second</u> plant locations, <u>the first detector comprising a temperature detector, and the second detector comprising a detector to <u>detect a said conditions and/or events including at least two or more of the</u> condition[[s]] or event[[s]] selected from the group consisting of <u>a fugitive</u> emission[[s]], <u>temperatures</u>, <u>a</u> level[[s]], and <u>a pressure[[s]]</u>;</u>
- at least [[one]] two battery-powered radio frequency transmitters mounted at the first and second plant location[[s]] in said plant in electrical communication with said\_at least [[one]] the first and second detectors, asid transmitters having [[a]] transmittable identification codes and wirelessly transmitting signals relative to said identification codes, the detectors, and condition of the battery batteries to a location remote from the first and second plant locations;
- a central processing location remote from the first <u>and second</u> plant locations for receiving and processing signals from said battery-powered transmitters in electrical communication with said detectors, said signals relative to the identification codes, [[a]] conditions or events detected at the first <u>and second</u> locations in said plant, and the <u>battery batteries</u>; and
- a third at least one second transmitter in communication with said central processing location, said third second transmitter mounted at a second third plant location capable of wirelessly transmitting signals relative to a condition or event detected at the plant-location to the central processing location.

- (Currently Amended) The system of Claim 1, further comprising at least one more detector and/or sensor to detect and/or sense [[a]] one of the conditions or events at a fourth third plant location.
- (Previously Presented) The system of Claim 2, further comprising at least one transmitter in communication with said at least one more detector and/or sensor.
- (Currently Amended) The system of Claim 3, wherein the <u>at least two</u> [[one]] battery-powered radio frequency transmitters is-a <u>are</u> spread spectrum transmitters.
- (Currently Amended) The system of Claim 4, wherein the <u>at least two</u> [[one]] battery-powered radio frequency transmitters is-a <u>are</u> 900 megahertz spread spectrum transmitters.
- (Currently Amended) The system of Claim 1, wherein [[the]] one of the at least two battery-powered radio frequency transmitters is a 900 megahertz spread spectrum transmitter and transmits on predetermined time intervals.
- 7. (Currently Amended) The system of Claim 1, wherein said third at least one-other transmitter comprises a radio frequency transmitter.
- (Currently Amended) The system of Claim 7, wherein said third at-least one-other transmitter comprises a spread spectrum radio frequency transmitter.
- (Currently Amended) The system of Claim 8, wherein said third at-least one other—transmitter comprises a 900 megahertz spread spectrum radio frequency transmitter

- (Currently Amended) The system of Claim 4, wherein said third at-least one other transmitter comprises a 900 megahertz spread spectrum radio frequency transmitter
  - 11-18. (Cancelled)
- 19. (Currently Amended) The system of Claim 1, wherein [[the]] at least one of the detectors is positioned in communication with a pipe in said plant.
- 20. (Currently Amended) The system of Claim 1, wherein [[the]] at least one of the detectors is positioned in communication with a valve in said plant.
- 21. (Currently Amended) The system of Claim 1, wherein [[the]] at least one of the detectors is positioned in communication with an enclosure in said plant.
  - 22. (Cancelled)
- (Currently Amended) The system of Claim 1, wherein the at-least one second detector detects a pressure.
- (Currently Amended) The system of Claim 1, wherein the at-least-one second detector detects [[a]] level.
- (Currently Amended) The system of Claim 21, wherein the at least on second detector detects a fugitive emission level.
- 26. (Currently Amended) The system of Claim 23, further comprising at least a third second detector in said plant, said third second detector in electrical communication with at least one battery-powered radio frequency spread spectrum transmitter, said third second detector detecting temperature.

- 27. (Currently Amended) The system of Claim 21, wherein [[the]] at least one of the detectors detects emissions.
- 28. (Currently Amended) The system of Claim 21, wherein [[the]] at least one of the detectors is an adsorption detector.
- 29. (Currently Amended) The system of Claim 1, wherein [[the]] at least one of the detectors detects emissions.
- 30. (Currently Amended) The system of Claim 1, wherein [[the]] at least one of the detectors is positioned in communication with a pipe enclosure.
- (Currently Amended) The system of Claim 1, wherein [[the]] at least one of the detectors is positioned in communication with a valve stuffing box enclosure.
- 32. (Currently Amended) The system of Claim 1, wherein [[the]] at least one of the detectors is operable when a voltage from the battery is applied thereto, and [[the]] at least one of the battery powered radio frequency transmitters is a 900 megahertz spread spectrum radio frequency transmitter, said transmitter transmitting signals on predetermined time intervals, and transmits, when appropriate a low battery transmission signal.

- 33. (Currently Amended) A battery-powered system for monitoring and/or detecting events and/or conditions in a plant, said system comprisine:
  - an exhaustible power source comprising a battery, said battery supplying a voltage:
- a detector mounted at a first location in the plant, said detector operable when voltage from the battery is applied thereto and monitoring and/or detecting an event and/or a condition in the plant relating to an enclosure and/or an enclosed material in the plant;
- a first transmitter mounted at the first location in the plant, said transmitter operable when voltage from the battery is applied thereto, said transmitter in electrical communication with the detector, the transmitter wirelessly transmitting signals relating to an event and/or condition monitored and/or detected by the detector from the first location in the plant, and said transmitter wirelessly transmitting, when appropriate, a low battery signal:
- a second exhaustible power source comprising a battery, said battery supplying a voltage;
- a second transmitter mounted at a second location in the plant remote from the first location, said transmitter operable when a voltage is applied thereto by the second battery, said transmitter wirelessly transmitting signals relating to a monitored and/or detected event and/or condition in the plant, and said transmitter wirelessly transmitting, when appropriate, a low battery signal; and
- a central processing location remote from the first and second plant locations for receiving <u>and processing</u> signals from said first and second transmitters.
- 34. (Currently Amended) A system according to Claim 33, wherein the <u>enclosed material</u> monitored-and/or-detected-event and/or-condition-relates to an enclosure and the enclosure is enclosed in a pipe.
- 35. (Currently Amended) A system according to Claim 33, wherein the <u>enclosed</u>
  <u>material</u> <u>monitored-and/or-detected-event-and/or-condition-relates-to-an-enclosure-and-the-enclosure</u> is enclosed in a valve stuffing box.
  - 36. (Cancelled)

## 37. (Cancelled)

- 38. (Currently Amended) A system according to Claim\_33 [[37]], wherein the enclosed material is a liquid and the detector monitors and/or detects level.
- (Previously Presented) A system according to Claim 33, wherein the detector monitors and/or detects pressure.
- (Previously Presented) A system according to Claim 33, wherein the detector monitors and/or detects temperature.
- 41. (Previously Presented) A system according to Claim 33, wherein the detector monitors and/or detects more than one event and/or condition.
- 42. (Currently Amended) A system according to Claim 33, wherein the event and/or condition relates to an enclosure and the detector monitors and/or detects emissions from [[the]] an enclosure.
- (Previously Presented) A system according to Claim 42, wherein the detector further monitors and/or detects temperature.